

V9 FSE

PUERTAS DE CRISTAL
GLASS DOOR

ESPECIFICACIONES INSTALACIÓN

INSTALLATION FEATURES

Instalación <i>Installation</i>	_____	Sobreponer <i>Surface Mounting</i>
Largo <i>Length</i>	_____	145 mm
Ancho <i>Width</i>	_____	38 / 26 mm
Profundo <i>Depth</i>	_____	44 mm
Voltaje <i>Voltage</i>	_____	12-24 VDC
Consumo arranque <i>Current consumption start</i>	_____	12 VDC 1000 mA 24 VDC 500 mA
Consumo reposo <i>Current consumption standby</i>	_____	12 VDC 110 mA 24 VDC 55 mA

Funcionamiento <i>Function</i>	_____	Normal <i>Fail secure</i>
Monitorización* <i>Monitoring</i>	_____	Si <i>Yes</i>
Temporización <i>Timer settings</i>	_____	0 - 3 or 6 s
Ciclos testados <i>Tested cycles</i>	_____	500.000
Temperatura funcionamiento <i>Temperature working range</i>	_____	-20°C / +50° C

*Posición del cerrojo.
Latch position.

PLANO TÉCNICO

TECHNICAL DRAW

FUERZA DE RETENCIÓN = 1750lb (800kg)
HOLDING FORCE = 1750lb (800kg)

